

01E PROBE

Electric Field Probe: E field, 100 kHz ÷ 6.5 GHz

Key Features:

- Frequency range: 100 kHz ÷ 6.5 GHz
- Dynamic range: > 65 dB
- Directivity: Isotropic



Compatibility:

- NHT310F and NHT3DL meters

Typical Application:

- Wireless telecommunication systems such as mobile phone base stations, satellite communication equipment, Broadcasting equipment, Wi-Fi, Wi-Max, LTE and 5G
- Industrial ovens, welding systems, RF heating, tempering and drying systems
- Diathermy equipment and medical devices RF generators, NMR machines
- Power plants and related maintenance and control systems
- Sensitive site (hospital)
- Measurement systems for railway and round transport

Information subject to change without prior notice

MICRORAD

Piazza delle Azalee, 13/14 05018 – Orvieto (TR) - Italy
Tel. +39 0763 393291 /Fax. +39 0763 394423 info@microrad.it - www.microrad.it







01E PROBE

Electric Field Probe: E field, 100 kHz ÷ 6.5 GHz

Description:

The 01E probe is based on a set of three mutually orthogonal diode dipoles. The signal from the three dipoles is used by Microrad instruments to calculate the isotropic value of the field.

The 01E probe is able to detect both CW (Continuous Wave) and modulated signals in the frequency ranges from 100kHz to 6.5GHz, allowing operators to cover applications in the industrial, scientific, medical, telecommunications and power plants sectors.

The high sensitivity of this probe makes it ideal for protectionist measurement of human exposure to electric fields in both public and professional environments.

The introduction of the signal envelope sampling technique, carried out with the NHT3DL and NHT310F meters, allows not only a reliable reading of the field value, but also, for the first time, the graphical representation in the time domain of the form factor of the analyzed signal. This innovative technique opens up new analytical perspectives, allowing to distinguish and evaluate intermittent or pulse signals with important crest factors such as those typical of 5G mobile telephones or radar.

TECHNICAL SPECIFICATION	
Frequency range	100 kHz ÷ 6.5 GHz
Type of frequency response	Flat
Measurement range	0.2 ÷ 360 V/m (cw)
Dynamic range	65 dB
Sensor type	Diode dipoles
Directivity	Isotropic
Frequency response	± 1.5 dB (1 MHz ÷ 3 GHz)
	± 2.5 dB (3 GHz ÷ 6.5 GHz)
Linearity	± 0.5 dB (2 ÷ 200 V/m)
Isotropic response	± 0.5 dB (@100 MHz)
Pulse response	500 µs

GENERAL CHARACTERISTICS	
Recommended calibration interval	24 months
Operating temperature	-10°C ÷ 50°C
Size	327 x 60 Ø(mm)
Weight	120g
Country of origin	Italy

MICRORAD

Piazza delle Azalee, 13/14 05018 – Orvieto (TR) - Italy
Tel. +39 0763 393291 /Fax. +39 0763 394423 info@microrad.it - www.microrad.it